

Table of Contents

Categorized Listing

| | |
|--|-----------|
| HYDRAULIC | 1 |
| PIONEER 4000 SERIES INTERCHANGE | 1 |
| GENERAL PURPOSE ISO "A" | 1 |
| INTERNATIONAL INTERCHANGE ISO 160.28 | 2 |
| COUPLE UNDER PRESSURE | 2 |
| Coupler | 3 |
| Plug | 3 |
| INDUSTRIAL INTERCHANGE ISO "B" | 3 |
| DIAGNOSTIC COUPLERS | 4 |
| PNEUMATIC | 4 |
| 1/4" INDUSTRIAL INTERCHANGE SERIES TYPE "D" | 4 |
| 3/8" INDUSTRIAL SERIES TYPE "E" | 5 |
| 1/2" INDUSTRIAL INTERCHANGE | 6 |
| 1/4" AUTOMOTIVE STANDARD SERIES TYPE "C" | 7 |
| 3/8" AUTOMOTIVE STANDARD SERIES TYPE "G" | 9 |
| 1/2" AUTOMOTIVE STANDARD SERIES TYPE "F" | 10 |
| 1/4" SERIES LINCOLN LONG NOSE TYPE "A" | 11 |
| 1/4" SERIES (ARO SERIES) TYPE "B" | 12 |
| 1/4" SERIES (ARO PUSH-TO-CONNECT) TYPE "B" | 13 |
| 3/8" ARO SERIES (MAX WORKING PRESSURE 300 PSI) | 13 |
| 1/4" DIAMOND-U INTERCHANGE | 13 |
| COMBO COUPLER | 13 |
| STRAIGHT-THRU | 14 |
| GARDEN HOSE | 14 |
| FILTERS, REGULATORS, LUBRICATORS | 15 |
| FILTERS | 15 |
| REGULATORS | 15 |
| LUBRICATORS | 16 |
| COMBOS | 16 |
| BLOW GUNS | 17 |
| BLOW GUN | 17 |
| BLOW GUN ACCESSORIES | 17 |

Pneumatic Coupler Interchange

| Amflo | Camel | Bridgeport | Milton | Schrader | TruFlate | NAPA | Lincoln | Foster |
|--|--------|------------|--------|----------|----------|--------|---------|----------|
| 1/4" Series Lincoln Long Nose Type "A" | | | | | | | | |
| C27 | 61-486 | 61-486 | 790 | 3527 | 13-424 | 90-645 | NA | LN3103 |
| C28 | 61-548 | 61-548 | NA | 3528 | 13-434 | 90-644 | 815 | LN3003 |
| 1/4" Series Aro Type "B" | | | | | | | | |
| C37 | 61-527 | 61-527 | NA | 3525 | 13-324 | 90-614 | NA | 210-3103 |
| C38 | 61-526 | 61-526 | NA | 3526 | 13-334 | 90-612 | 862 | NA |
| C45 | 61-581 | 61-581 | NA | NA | NA | 90-679 | NA | 210-3103 |
| C46 | 61-518 | 61-518 | NA | NA | NA | 90-613 | NA | NA |
| 1/4" Series Automotive Type "C" | | | | | | | | |
| C1 | 61-524 | 61-524 | 786 | 3503 | 13-125 | 90-610 | NA | TF3103 |
| C2 | 61-523 | 61-523 | 785 | 3504 | 13-134 | 90-600 | NA | TF3003 |
| C2R | 61-487 | 61-487 | 787 | 3505 | 13-136 | 90-609 | NA | NA |
| 3/8" Series Automotive Type "G" | | | | | | | | |
| C5 | 61-554 | 61-554 | 1806 | 3515 | 13-604 | 90-656 | NA | TF4304 |
| C6 | 61-553 | 61-553 | 1805 | 3516 | 13-612 | 90-654 | NA | TF4204 |
| C7 | 61-478 | 61-478 | NA | NA | 13-602 | 90-684 | NA | TF4104 |
| C8 | 61-476 | 61-476 | 1803 | 3521 | 13-610 | 90-686 | NA | TF4004 |
| 1/2" Series Automotive Type "F" | | | | | | | | |
| C9 | 61-564 | 61-564 | 1816 | 3511 | 13-704 | 90-664 | 651008 | 5305 |
| C10 | 61-563 | 61-563 | 1815 | 3512 | 13-712 | 90-662 | 652008 | 5205 |
| C10-23 | 61-472 | 61-472 | 1813 | 3516 | 13-710 | 90-690 | 652006 | 5005 |
| 1/4" Series Industrial Type "D" | | | | | | | | |
| C20 | 61-573 | 61-573 | 715 | 5142-12 | 13-234 | 90-670 | 612004 | 3003 |
| C21 | 61-574 | 61-574 | 716 | 5141-12 | 13-224 | 90-672 | 611004 | 3103 |
| C20-23 | NA | 61-103 | 718 | 5263-12 | 13-236 | NA | 612006 | 3203 |
| C21-03 | NA | 61-101 | 719 | 5140-12 | 13-226 | NA | 631006 | 3303 |
| C40 | 61-013 | 61-013 | 755 | 5138-12 | 13-755 | 90-615 | NA | FM3003 |
| C41 | 61-011 | 61-011 | 756 | 5139-12 | 13-756 | 90-617 | NA | FM3103 |
| 3/8" Series Industrial Type "E" | | | | | | | | |
| C25 | 61-483 | 61-483 | 1836 | NA | 13-526 | 90-682 | 641006 | 4304 |
| C26 | 61-482 | 61-482 | 1865 | 3541 | 13-536 | 90-680 | 642006 | 4204 |
| C25-02 | NA | 61-110 | NA | NA | NA | 90-625 | 641004 | 4104 |
| C25-04 | NA | 61-111 | NA | NA | NA | 90-627 | 641008 | NA |
| 1/2" Series Industrial Type "H" | | | | | | | | |
| C9-03 | NA | 61-473 | 1814 | NA | 13-702 | 90-668 | 651106 | 5105 |
| C9 | NA | 61-564 | 1816 | 3511 | 13-704 | 90-664 | 651008 | 5305 |
| C9-06 | NA | 61-460 | NA | NA | NA | NA | 651012 | NA |
| C10 | NA | 61-563 | 1815 | 3512 | 13-712 | 90-662 | 652008 | 5205 |

Pneumatic Plug Interchange

| Amflo | Camel | Bridgeport | Milton | Schrader | TruFlate | NAPA | Lincoln | Foster |
|--|--------|------------|--------|----------|----------|--------|---------|--------|
| 1/4" Series Lincoln Long Nose Type "A" | | | | | | | | |
| CP27 | 61-550 | 61-550 | 791 | 3531 | 12-424 | 90-648 | 11659 | LN10 |
| CP28 | 61-551 | 61-551 | 792 | 3531 | 12-434 | 90-650 | 11661 | LN11 |
| 1/4" Series Aro Type "B" | | | | | | | | |
| CP37 | 61-528 | 61-528 | 777 | 3529 | 12-324 | 90-618 | 13329 | 210-10 |
| CP38 | 61-529 | 61-529 | 778 | 3530 | 12-334 | 90-620 | 13331 | 210-11 |
| 1/4" Series Automotive Type "C" | | | | | | | | |
| CP1 | 61-538 | 61-538 | 783 | 3506 | 12-124 | 90-626 | NA | TF10 |
| CP2 | 61-539 | 61-539 | 784 | 3504 | 13-134 | 90-600 | NA | TF11 |
| 3/8" Series Automotive Type "G" | | | | | | | | |
| CP5 | 61-558 | 61-558 | 1807 | 3517 | 12-604 | 90-658 | NA | TF42 |
| CP6 | 61-559 | 61-559 | 1808 | 3518 | 12-612 | 90-660 | NA | TF43 |
| CP7 | 61-480 | 61-480 | 1809 | 3519 | 12-602 | 90-685 | NA | TF40 |
| CP8 | 61-481 | 61-476 | 1810 | 3520 | 12-610 | 90-687 | NA | TF41 |
| 1/2" Series Automotive Type "F" | | | | | | | | |
| CP9 | 61-568 | 61-568 | 1817 | 3513 | 12-704 | 90-666 | NA | 54-5 |
| CP10 | 61-569 | 61-569 | 1818 | 3514 | 12-712 | 90-668 | NA | 55-5 |
| CP1023 | 61-475 | 61-475 | 1820 | NA | 12-710 | 90-691 | NA | 53-5 |
| 1/4" Series Industrial Type "D" | | | | | | | | |
| CP20 | 61-579 | 61-579 | 728 | 5139-11 | 12-234 | 90-676 | 630204 | 11-3 |
| CP21 | 61-578 | 61-578 | 727 | 5138-11 | 12-224 | 90-674 | 630104 | 10-3 |
| CP20-23 | NA | 61-103 | 732 | 5263-11 | NA | NA | 630106 | 15-3 |
| CP21-03 | 61-535 | 61-535 | 733 | NA | 12-226 | 90-677 | 631006 | 14-3 |
| 3/8" Series Industrial Type "E" | | | | | | | | |
| CP25 | 61-484 | 61-484 | 1837 | 3542 | 12-526 | 90-683 | 640106 | 42-4 |
| CP26 | 61-485 | 61-485 | 1838 | 3543 | 12-536 | 90-681 | 640206 | 43-4 |
| CP25-02 | NA | 61-117 | 1839 | NA | NA | NA | 640104 | 40-4 |
| CP25-04 | NA | 61-118 | NA | NA | NA | NA | 640108 | NA |
| 1/2" Series Industrial Type "H" | | | | | | | | |
| CP17-03 | 61-133 | 61-133 | 1819 | 3537 | 12-702 | 90-689 | NA | 52-5 |
| CP17-03 | 61-134 | 61-134 | 1817 | 3513 | 12-704 | 90-666 | 630204 | 54-5 |
| CP17-06 | NA | 61-135 | NA | NA | NA | NA | NA | NA |

HYDRAULIC

PIONEER 4000 SERIES INTERCHANGE

Double Shut-Off, General Purpose
Hydraulic Couplers with hardened steel
poppets
Two way coupler

COUPLER



| ITEM | BODY | THREAD SIZE |
|-------|------|-------------|
| C2-16 | 1/4 | 1/4 |
| C3-21 | 3/8 | 3/8 |
| C4-10 | 1/2 | 7/8-14 ORB |
| C4-26 | 1/2 | 1/2 |
| C4-31 | 1/2 | 3/4 |
| C4-8 | 1/2 | 3/4-16 ORB |
| C6-31 | 3/4 | 3/4 |
| C8-36 | 1 | 1 |

PLUG



| ITEM | BODY | THREAD SIZE |
|-------|------|-------------|
| P2-16 | 1/4 | 1/4 |
| P3-21 | 3/8 | 3/8 |
| P4-10 | 1/2 | 7/8-14 ORB |
| P4-26 | 1/2 | 1/2 |
| P4-31 | 1/2 | 3/4 |
| P4-8 | 1/2 | 3/4-16 ORB |
| P6-31 | 3/4 | 3/4 |
| P8-36 | 1 | 1 |

GENERAL PURPOSE ISO "A"

Double-Shut-Off, General Purpose.
Interchangeable with all leading "general
purpose" couplers.

Working Pressure:
1/4"= 5000psi
3/8"-1"=4000psi

COUPLER



| ITEM | BODY | THREAD SIZE |
|-----------|------|-------------|
| CA5602-16 | 1/4 | 1/4-18 |
| CA5603-21 | 3/8 | 3/8-18 |
| CA5604-26 | 1/2 | 1/2-14 |
| CA5606-31 | 3/4 | 3/4-14 |
| CA5608-36 | 1 | 1-11 1/2 |

| ITEM | BODY | THREAD SIZE |
|-----------|------|-------------|
| PA5602-16 | 1/4 | 1/4-18 |
| PA5603-21 | 3/8 | 3/8-18 |
| PA5604-26 | 1/2 | 1/2-14 |
| PA5606-31 | 3/4 | 3/4-14 |
| PA5608-36 | 1 | 1-11 1/2 |

INTERNATIONAL INTERCHANGE ISO 160.28

Double-Shut-Off, Flush face
International interchange design intended for hydraulic service where fluid loss is undesirable.

Working pressure:
1/4" body=4000psi
3/8"-1" body=3000psi

COUPLER



| ITEM | BODY | THREAD SIZE |
|--------|------|----------------|
| EC2-16 | 1/4 | 1/4 |
| EC3-21 | 3/8 | 3/8 |
| EC3-26 | 3/8 | 1/2 |
| EC4-12 | 1/2 | 1-1/16 -12 ORB |
| EC4-26 | 1/2 | 1/2 |
| EC4-31 | 1/2 | 3/4 |
| EC6-31 | 3/4 | 3/4 |

PLUG



| ITEM | BODY | THREAD SIZE |
|--------|------|----------------|
| EP2-16 | 1/4 | 1/4 |
| EP3-21 | 3/8 | 3/8 |
| EP3-26 | 3/8 | 1/2 |
| EP4-12 | 1/2 | 1-1/16 -12 ORB |
| EP4-26 | 1/2 | 1/2 |
| EP4-31 | 1/2 | 3/4 |
| EP6-31 | 3/4 | 3/4 |

COUPLE UNDER PRESSURE

Suitable for coupling and uncoupling at pressures up to 500psig.

COUPLER WITH WINGS



| ITEM | BODY | THREAD SIZE |
|--------|-------|-------------|
| 51W-12 | 3/4 | 3/4 |
| 51W-16 | 1 | 1 |
| 51W-20 | 1 1/4 | 1-1/4 |
| 51W-8 | 3/4 | 1/2 |

PLUG WITHOUT FLANGE



| ITEM | BODY | THREAD SIZE |
|--------|-------|-------------|
| 51P-12 | 3/4 | 3/4 |
| 51P-16 | 1 | 1 |
| 51P-20 | 1 1/4 | 1-1/4 |
| 51P-8 | 3/4 | 1/2 |

| ITEM | BODY | TYPE |
|---------|------|-----------|
| 51DC-16 | 1 | DUST CAP |
| 51DP-16 | 1 | DUST PLUG |

Coupler

Up to 14,000 PSI working pressure
Connect/disconnect under pressure
Interchanges with Parker, Faster, Safeway and Enerpac



| ITEM | BODY | THREAD SIZE |
|--------|------|-------------|
| 3050-2 | 1/4 | 1/4 |
| 3050-3 | 3/8 | 3/8 |

Plug

| ITEM | BODY | THREAD SIZE |
|--------|------|-------------|
| 3010-2 | 1/4 | 1/4 |
| 3010-3 | 3/8 | 3/8 |

INDUSTRIAL INTERCHANGE ISO "B"

These couplers and plus both have fast-acting poppet valves in them to effectively prevent fluid loss on disconnect.

COUPLER



| ITEM | BODY | THREAD SIZE |
|------------|------|-------------|
| TH1-11 | 1/8 | 1/8 |
| TH2-16 | 1/4 | 1/4 |
| TH3-21 | 3/8 | 3/8 |
| TH4-26 | 1/2 | 1/2 |
| TH6-31 | 3/4 | 3/4 |
| TH6-31-002 | 3/4 | 3/4 |
| TH8-36 | 1 | 1 |
| TH8-36-002 | 1 | 1 |

PLUG



| ITEM | BODY | THREAD SIZE |
|--------|------|-------------|
| TK1-11 | 1/8 | 1/8 |

| ITEM | BODY | THREAD SIZE |
|------------|------|-------------|
| TK2-16 | 1/4 | 1/4 |
| TK3-21 | 3/8 | 3/8 |
| TK4-26 | 1/2 | 1/2 |
| TK6-31 | 3/4 | 3/4 |
| TK6-31-002 | 3/4 | 3/4 |
| TK8-36 | 1 | 1 |
| TK8-36-002 | 1 | 1 |

DIAGNOSTIC COUPLERS

Diagnostic test port couplers are designed for permanent hydraulic system installation to provide an easy and convenient means of connection with pressure gauges, temperature sensors and other diagnostic instruments.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| KC1-11 | FEMALE | 1/8 |
| KC1-15 | MALE | 1/4 |
| KC1-16 | FEMALE | 1/4 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| KP1-10 | MALE | 1/8 |
| KP1-11 | FEMALE | 1/8 |
| KP1-15 | MALE | 1/4 |
| KP1-16 | FEMALE | 1/4 |
| KP1-4 | MALE | 7/16-20 ORB |
| KP1-6 | MALE | 9/16-18 ORB |

PNEUMATIC

1/4" INDUSTRIAL INTERCHANGE SERIES TYPE "D"

Plated steel couplers have hardened steel balls and stainless steel springs. The plugs are heat treated to reduce wear on critical mating surfaces. The Industrial Interchange Series couplers interchange with Aro, Foster, Milton as well as units produced by other manufactures.

Maximum working pressure 300psi.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|-----------|-------------|-------------|
| AMC21 | MALE | 1/4 |
| AMC21-03 | MALE | 3/8 |
| AMC21-03B | MALE | 3/8 |
| AMC21B | MALE | 1/4 |

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMC20 | FEMALE | 1/4 |
| AMC20-23 | FEMALE | 3/8 |
| AMC20B | FEMALE | 1/4 |

COUPLER



| ITEM | BARB |
|-------------|------|
| AMC20-42 | 1/4 |
| AMC20-42B | 1/4 |
| AMC20-42L | 1/4 |
| AMC20-42LBP | 1/4 |
| AMC20-44 | 3/8 |
| AMC20-44B | 3/8 |
| AMC20-44L | 3/8 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|---------------|-------------|-------------|
| AMCP21 | MALE | 1/4 |
| AMCP21-03 | MALE | 3/8 |
| AMCP21-03B | MALE | 3/8 |
| AMCP21-03-RET | MALE | 3/8 |
| AMCP21B | MALE | 1/4 |
| AMCP21SW | MALE | 1/4 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|-----------|-------------|-------------|
| AMCP20 | FEMALE | 1/4 |
| AMCP20-23 | FEMALE | 3/8 |
| AMCP20B | FEMALE | 1/4 |
| AMCP20SW | FEMALE | 3/8 |

PLUG



| ITEM | BARB |
|------------|------|
| AMCP21-42 | 1/4 |
| AMCP21-42L | 1/4 |
| AMCP21-44 | 3/8 |
| AMCP21-44B | 3/8 |
| AMCP21-44L | 3/8 |

3/8" INDUSTRIAL SERIES TYPE "E"

These couplers and plugs are intended for compressed air lines only. The maximum working pressure is rated 300psi.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMC25 | MALE | 3/8 |
| AMC25-02 | MALE | 1/4 |
| AMC25-04 | MALE | 1/2 |

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMC26 | FEMALE | 3/8 |
| AMC26-22 | FEMALE | 1/4 |
| AMC26-24 | FEMALE | 1/2 |

COUPLER

| ITEM | BARB |
|-----------|------|
| AMC26-44 | 3/8 |
| AMC26-44L | 3/8 |
| AMC26-45 | 1/2 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|-----------|-------------|-------------|
| AMCP25 | MALE | 3/8 |
| AMCP25-02 | MALE | 1/4 |
| AMCP25-04 | MALE | 1/2 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|-----------|-------------|-------------|
| AMCP26 | FEMALE | 3/8 |
| AMCP26-22 | FEMALE | 1/4 |
| AMCP26-24 | FEMALE | 1/2 |

PLUG



| ITEM | BARB |
|------------|------|
| AMCP25-44 | 3/8 |
| AMCP25-44L | 3/8 |
| AMCP25-45 | 1/2 |

1/2" INDUSTRIAL INTERCHANGE

These couplers and plugs are intended for use on compressed air lines. They have a maximum working pressure rated at 300psi.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|---------|-------------|-------------|
| AMC9 | MALE | 1/2 |
| AMC9-03 | MALE | 3/8 |

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMC10 | FEMALE | 1/2 |
| AMC10-23 | FEMALE | 3/8 |

COUPLER

| ITEM | BARB |
|----------|------|
| AMC10-45 | 1/2 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|-----------|-------------|-------------|
| AMCP17 | MALE | 1/2 |
| AMCP17-03 | MALE | 3/8 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| AMCP18 | FEMALE | 1/2 |

PLUG



| ITEM | BARB |
|-----------|------|
| AMCP17-45 | 1/2 |

1/4" AUTOMOTIVE STANDARD SERIES TYPE "C"

Plated steel couplers have hardened steel balls and stainless steel springs. Plugs are heat treated to reduce wear on critical mating surfaces. The Automotive Series couplers interchange with Tru-Flate 10 and 100 type series as well as units produced by other manufacturers.

Maximum working pressure 300psi.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|---------|-------------|-------------|
| AMC1 | MALE | 1/4 |
| AMC1-03 | MALE | 3/8 |
| AMC1B | MALE | 1/4 |

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|---------|-------------|-------------|
| AMC2 | FEMALE | 1/4 |
| AMC2-23 | FEMALE | 3/8 |
| AMC2B | FEMALE | 1/4 |

COUPLER

| ITEM | BARB |
|----------|------|
| AMC2-42 | 1/4 |
| AMC2-44 | 3/8 |
| AMC2-44B | 3/8 |
| AMC2-44L | 3/8 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMCP1 | MALE | 1/4 |
| AMCP1-03 | MALE | 3/8 |
| AMCP1B | MALE | 1/4 |
| AMCP1SW | MALE | 1/4 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMCP2 | FEMALE | 1/4 |
| AMCP2-23 | FEMALE | 3/8 |
| AMCP2B | FEMALE | 1/4 |

PLUG

| ITEM | BARB |
|-----------|------|
| AMCP1-42 | 1/4 |
| AMCP1-42L | 1/4 |
| AMCP1-44 | 3/8 |
| AMCP1-44L | 3/8 |

3/8" AUTOMOTIVE STANDARD SERIES TYPE "G"

Plated steel couplers have hardened steel balls and stainless steel springs. Plugs are heat treated to reduce wear on critical mating surfaces.

Maximum working pressure 300psi.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|---------|-------------|-------------|
| AMC5 | MALE | 3/8 |
| AMC5-04 | MALE | 1/2 |
| AMC7 | MALE | 1/4 |

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|---------|-------------|-------------|
| AMC6 | FEMALE | 3/8 |
| AMC6-24 | FEMALE | 1/2 |
| AMC8 | FEMALE | 1/4 |

COUPLER

| ITEM | BARB |
|---------|------|
| AMC6-44 | 3/8 |
| AMC6-45 | 1/2 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMCP5 | MALE | 3/8 |
| AMCP7 | MALE | 1/4 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMCP6 | FEMALE | 3/8 |
| AMCP6-24 | FEMALE | 1/2 |
| AMCP8 | FEMALE | 1/4 |

PLUG

| ITEM | BARB |
|-----------|------|
| AMCP5-42L | 1/4 |
| AMCP5-44 | 3/8 |
| AMCP5-44L | 3/8 |

1/2" AUTOMOTIVE STANDARD SERIES TYPE "F"

Plated steel couplers have hardened steel balls and stainless steel springs. Plugs are heat treated to reduce wear on critical mating surfaces.

Maximum working pressure 300psi.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|---------|-------------|-------------|
| AMC9 | MALE | 1/2 |
| AMC9-03 | MALE | 3/8 |

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMC10 | FEMALE | 1/2 |
| AMC10-23 | FEMALE | 3/8 |

COUPLER

| ITEM | BARB |
|----------|------|
| AMC10-45 | 1/2 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMCP9 | MALE | 1/2 |
| AMCP9-03 | MALE | 3/8 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|-----------|-------------|-------------|
| AMCP10 | FEMALE | 1/2 |
| AMCP10-23 | FEMALE | 3/8 |

PLUG

| ITEM | BARB |
|----------|------|
| AMCP9-45 | 1/2 |

1/4" SERIES LINCOLN LONG NOSE TYPE "A"

Plated steel couplers have hardened steel balls and stainless steel springs. Plugs are heat treated to reduce wear on critical mating surfaces. The Lincoln Series of plugs are easily identified by the long plug end. The couplers are identified with one narrow and one wide groove on the sleeve. Couplers interchange with Lincoln as well as units produced by other manufactures.

Maximum working pressure 300psi.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC27 | MALE | 1/4 |

COUPLER

| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC28 | FEMALE | 1/4 |

PLUG

| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| AMCP27 | MALE | 1/4 |

PLUG

| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| AMCP28 | FEMALE | 1/4 |

1/4" SERIES (ARO SERIES) TYPE "B"

The Aro Series of plugs are easily identified by the distinct appearance of the plug. The couplers are identified with one wide groove on the sleeve. Couplers interchange with Aro 210 series as well as units produced by other manufactures.

Maximum working pressure 300psi.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMC37 | MALE | 1/4 |
| AMC37-03 | MALE | 3/8 |

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMC38 | FEMALE | 1/4 |
| AMC38-23 | FEMALE | 3/8 |
| AMC38B | FEMALE | 1/4 |

COUPLER

| ITEM | BARB |
|----------|------|
| AMC38-42 | 1/4 |
| AMC38-44 | 3/8 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|-----------|-------------|-------------|
| AMCP37 | MALE | 1/4 |
| AMCP37-03 | MALE | 3/8 |
| AMCP37B | MALE | 1/4 |

PLUG

| ITEM | THREAD TYPE | THREAD SIZE |
|-----------|-------------|-------------|
| AMCP38 | FEMALE | 1/4 |
| AMCP38-23 | FEMALE | 3/8 |
| AMCP38B | FEMALE | 1/4 |

PLUG

| ITEM | BARB |
|------------|------|
| AMCP37-42 | 1/4 |
| AMCP37-44B | 3/8 |
| AMCP37-44L | 3/8 |

1/4" SERIES (ARO PUSH-TO-CONNECT) TYPE "B"

Push-to-connect couplers are automatically connected by pushing the plug into the coupler. Especially useful for hooking up implements. Allows one hand operation.

Maximum working pressure 300psi

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC45 | MALE | 1/4 |

COUPLER

| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC46 | FEMALE | 1/4 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| AMCP37 | MALE | 1/4 |

PLUG

| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| AMCP38 | FEMALE | 1/4 |

3/8" ARO SERIES (MAX WORKING PRESSURE 300 PSI)

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC35 | MALE | 3/8 |

COUPLER

| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC36 | FEMALE | 1/4 |

PLUG

| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| AMCP35 | MALE | 3/8 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| AMCP36 | FEMALE | 3/8 |

1/4" DIAMOND-U INTERCHANGE

COUPLER

| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC31 | MALE | 1/4 |

COUPLER

| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC30 | FEMALE | 1/4 |

PLUG

| ITEM | THREAD TYPE | THREAD SIZE |
|--------|-------------|-------------|
| AMCP33 | MALE | 1/4 |
| AMCP34 | MALE | 1/4 |

COMBO COUPLER

The solution for coupler confusion. Now one coupler fits 1/4" Aro Style, 1/4" Automotive Standard and 1/4" Industrial Interchange plugs. Convenient push-to-connect brass design. Temperature range -40F to +240F.

Maximum working pressure 250psi.

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC61 | MALE | 1/4 |

| ITEM | THREAD TYPE | THREAD SIZE |
|-------|-------------|-------------|
| AMC60 | FEMALE | 1/4 |

STRAIGHT-THRU

These couplers and plugs have no valves. Smooth straight-thru bore allows maximum flow. Made from solid brass bar stock. Couplers have stainless steel springs and balls. Excellent for carpet cleaners, vacuum service and pressure washers.

Straight-thru pressure specifications:
Brass-1/8"=2500, 1/4"=5200, 3/8"=2700, 1/2"=2200
Steel-1/8"=2600, 1/4"=5500, 3/8"=3500, 1/2"=2700

COUPLER



| ITEM | THREAD TYPE | THREAD SIZE |
|---------|-------------|-------------|
| AMCST1B | MALE | 1/8 |
| AMCST3B | MALE | 1/4 |

COUPLER

| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMCST17B | FEMALE | 1/4 |
| AMCST4B | FEMALE | 1/4 |
| AMCST6B | FEMALE | 3/8 |
| AMCST8B | FEMALE | 1/2 |

PLUG



| ITEM | THREAD TYPE | THREAD SIZE |
|----------|-------------|-------------|
| AMCPST3B | MALE | 1/4 |
| AMCPST5 | MALE | 3/8 |
| AMCPST5B | MALE | 3/8 |
| AMCPST7B | MALE | 1/2 |

PLUG

| ITEM | THREAD TYPE | THREAD SIZE |
|-----------|-------------|-------------|
| AMCPST17B | FEMALE | 1/4 |
| AMCPST2B | FEMALE | 1/8 |
| AMCPST6 | FEMALE | 3/8 |
| AMCPST6B | FEMALE | 3/8 |
| AMCPST8B | FEMALE | 1/2 |

GARDEN HOSE

Coupler has female garden hose threads. The plug has male garden hose thread.



GHP GHC

| ITEM |
|------|
| GHC |
| GHP |

FILTERS, REGULATORS, LUBRICATORS

FILTERS



Filters:

Standard

| Ports | SCFM |
|-------|------|
| ¼-3/8 | 70 |
| ½-3/4 | 150 |
| 1 | 425 |

Specifications

Fluid: Compressed Air
Max Inlet Pressure—
Poly Bowl: 150psig
Metal Bowl: 250psig
Max Temperature—
Poly Bowl: 125F
Metal Bowl: 175F

Regulators:

| Ports | SCFM |
|------------------|------|
| ¼ (miniature) | 20 |
| ¼-3/8" (compact) | 50 |
| Standard | |
| ¼-3/8 | 70 |
| ½-3/4 | 150 |
| 1 | 425 |

Specifications

Fluid: Compressed Air
Max Inlet Pressure: 300psig
Temperature Range—
Mini/compact: 0-150F
Standard: 0-175F
Gauge Port—
Mini/compact: 2-1/8" NPT (full flow)
Standard: 2-1/4" NPT (full flow)
Outlet Range (all) — 5-125 psi

Lubricators:

Standard

| Ports | SCFM |
|-------|------|
| ¼-3/8 | 35 |
| ½-3/4 | 150 |
| 1 | 425 |

Specifications

Fluid: Compressed Air
Max Inlet Pressure—
Poly Bowl: 150psig
Metal Bowl: 250psig
Max Temperature:
Poly Bowl: 125F
Metal Bowl: 175F

| ITEM | PORT | BOWL | BODY |
|-------|------|-------|------|
| 4010A | 1/4 | POLY | 3/8 |
| 4011A | 1/4 | METAL | 3/8 |
| 4020A | 3/8 | POLY | 3/8 |
| 4021A | 3/8 | METAL | 3/8 |
| 4030 | 1/2 | POLY | 1/2 |
| 4031 | 1/2 | METAL | 1/2 |
| 4032 | 3/4 | POLY | 1/2 |
| 4040 | 3/4 | METAL | 1/2 |
| 4041 | 3/4 | METAL | 1 |
| 4050 | 1 | METAL | 1 |

REGULATORS

| ITEM | TYPE | PORT | GAUGE | BODY |
|------|------|------|-------|------|
| 3100 | | 1/4 | | MINI |
| 4100 | | 1/4 | | MINI |

REGULATORS

| ITEM | TYPE | PORT | GAUGE | BODY |
|-------|----------------|------|-------|------|
| 4100D | | 1/4 | YES | MINI |
| 4102 | NON-REPAIRABLE | 1/4 | | MINI |
| 4115A | | 1/4 | | 3/8 |
| 4125A | | 3/8 | | 3/8 |
| 4135 | | 1/2 | | 1/2 |
| 4145 | | 3/4 | | 1/2 |
| 4155 | | 1 | | 1 |

LUBRICATORS

| ITEM | TYPE | PORT | BOWL | BODY |
|-------|---------|------|-------|------|
| 4211A | OIL FOG | 1/4 | METAL | 3/8 |
| 4220A | OIL FOG | 3/8 | POLY | 3/8 |
| 4221A | OIL FOG | 3/8 | METAL | 3/8 |
| 4231 | OIL FOG | 1/2 | METAL | 1/2 |
| 4241 | OIL FOG | 3/4 | METAL | 1/2 |
| 4242 | OIL FOG | 1 | POLY | 1 |

COMBOS



| ITEM | TYPE | PORT | BOWL | BODY |
|-------|-------------------------------|------|------|------|
| 4310A | FILTER, REGULATOR | 1/4 | POLY | 3/8 |
| 4405 | FILTER, REGULATOR, LUBRICATOR | 1/4 | POLY | MINI |
| 4420A | FILTER, REGULATOR, LUBRICATOR | 3/8 | POLY | 3/8 |
| 4430 | FILTER, REGULATOR, LUBRICATOR | 1/2 | POLY | 1/2 |

BLOW GUNS

BLOW GUN



AM226



AM204-30



AM201



AM221 NOZZLE



AM200 TIP

| ITEM | TYPE |
|----------|--------------------------|
| AM201 | RUBBER TIPPED |
| AM204-30 | GROSS-DRILLED TIP BYPASS |
| AM206-30 | HEAVY-DUTY |
| AM217 | ADJUSTABLE POCKET |
| AM226 | BOOSTER |

BLOW GUN ACCESSORIES

| ITEM | TYPE |
|--------|--------------------------|
| AM200T | STANDARD REPLACEMENT TIP |
| AM221 | SIPHON NOZZLE TIP |